

HUAWIN PRECISION LTD.

External Spline Grinder

EG1260

External Spline Grinder EG1260

- Equipped with Interactive HMI for upgraded performance and user-friendly operations.
- Quick dressing process realized by moveable rotary dressing device
- DD motor of C-axis with zero-backspace lash.
- High precision applied to detect workpiece automatically



option



option



HUAWIN PRECISION LTD.


External Spline Grinder

EG1260

EG1260 External spline Grinder

Machine Specifications

Workpiece		Spec	Unit	Remark
1	Min.spline minor diameter	Φ20	mm	
	Min.spline width	4	mm	
	Max.spline major diameter	120	mm	
	Max.spline width	20	mm	
	Number of spline	1~99		
Stroke				
2	X-axis	70	mm	
	Y-axis	150	mm	
	U-axis	40	mm	
	Z-axis	600	mm	
3	C-axis (DD motor)	Rated torque	500	N.m
		center distance	800	mm
4	S1-axis	Power	7.5	Kw
		Max.speed	10000	r/min
5	Power capacity	<20	KVA	
6	Air pressure source	Rated flow	30	L/min
		Pressure	0.5	MPa
7	Floor Sapce (L×W×H)	2200x1650x2000		mm
8	Net Weight	4500	kg	



B : S1-axis
 C : C-axis
 X : Feeding-axis
 Y : Feeding-axis
 Z : Feeding-axis
 U : Rotary dressing device



333 桃園市龜山區大坑路二段30號B區

Unit B, No.30, Sec.2, DaKeng Rd., Guishan Dist., Taoyuan City, Taiwan

Tel: +886-3326-4555 Fax: +886-3357-9756

http://huawin-precision.com.tw E-mail: info@huawinprecision.com

www.huawin-precision.com.tw

